



| 尺寸公差(mm) | | | | | 0.05/10 ±T |
|--------------|----------------|-----------------|------------------|-------|---------------|
| 0 ~ 30 | >30 ~ 60 | >60 ~ 100 | >100 ~ 150 | >150 | |
| ±0.20 | ±0.30 | ±0.50 | ±0.70 | ±1.00 | |

| | |
|------------------------------------|-------------------------------------|
| Rated current | 12A |
| Rated voltage | 300V |
| Coil/Contact dielectric voltage | 2500V/S |
| Dielectric voltage between contact | 2500V/S |
| Screw torque | 1.0Nm |
| External connection wire | 20-14/0.5-2.5W G/mm ² |
| Ambient temperature | -40~+85°C |
| Key controlled symbol | * |

Conform to RoHS

Printing for laser marking, printing content is clear ,no broken line,ect

Seal literal reference according to the foot position in the drawing

| 1 | DPKF08A-E3-00A(H)-N | 30019000030 | 1 | | |
|----------------------|---------------------|---|-----|--|-------|
| NO. | DESCRIPTION | MATERIAL NO. | QTY | MATERIAL | NOTES |
| MATERIAL: / | | SURFACE: / | | | |
| MAT.NO.: 30020000049 | | 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD | | | |
| STATUS: / | | | | | |
| APPD: | | Description: DPKF08A-E3-00A(H) | | | |
| CHKD: | | | | | |
| DRFT: / | | DRAWING NO.: 30000357 | | REV | TO-1 |
| SIZE: A4 | | mm (inch) | | TYPE: PRODUCT DRAWING SCALE: 1:1 SHEET 1/1 | |

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility, model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将承担法律责任。本公司保留就涉及发明、实用新型和外专利的所有权利。